

## CORAL BRUSH ACTIV SPECIFICATIONS

SPECIFICATIONS	
Type of manufacture	Tufted, 5/32" cut pile
Width	200cms (roll length 27.5M)
Design/colour	Multi coloured designed/coloured
Pile material	100% polyamide
Primary Backing	Non-woven polyester
Backing	Everfort <sup>®</sup> vinyl
Pile Weight	Approx. 920 g/m <sup>2</sup>
Pile density ISO 8543	Approx. 0.106 g/cm <sup>3</sup>
Pile thickness ISO 1766	Approx. 7.0mm
Total weight ISO 8543	Approx. 3700 g/m <sup>2</sup>
Total thickness ISO 1765	Approx. 10 mm
Number of tufts per m <sup>2</sup> ISO 1763	Approx. 68,000
Wear classification EN 1307	Class 4 Heavy Commercial
Comfort classification EN 1307	Class 3
Antistatic EN 1815	< 2 kV (antistatic)
Electrical vertical resistance ISO/DIS 10965	Approx. 10 <sup>11</sup> Ω
Acoustic insulation ISO 140-8	Δ Lw= 37 dB
Acoustic absorption ISO 354	Freq. Hz. 125 250 500 1000 2000 4000
Thermal resistance ISO 8302	0.18 m <sup>2</sup> K/W
<b>Colour fastness to:</b>	
• Rubbing ISO 105 X12	5
• Water ISO 105 E01	5
• Light ISO 105 B02	7
• Sea water ISO 105 E02	4
• Organic solvents ISO 105 X05	4-5
• Shampoo BS 1006	4
• Chlorinated water ISO105	1
<b>Slip resistance:</b>	
AS/NZS 4586 – 1999	Oil wet ramp: Class R12
<b>Fire resistance:</b>	
• BS4790: 1972	Class low radius
• AS / ISO 9239.1 – 2003	CHF value: 5.7 kW/m <sup>2</sup> . Smoke value: 594%min.
• ASTM E648-91a	Class 1