



PEDIGREE

Carpets by **KARNDEAN**

PEDIGREE UV-TEX SPECIFICATIONS

SPECIFICATIONS	
Description	Commercial heavy duty fibre bonded carpeting with a velour surface profile or rib surface profile.
Composition	100% stabilized polypropylene fibres.
Backing	Acrylic coated
Surface pile weight	700 grams per m ²
Total weight	950 grams per m ²
Overall thickness	6.0mm
Suitability	Commercial heavy duty indoor /outdoor use. Use suitable protective mats under chairs incorporating castor wheels.
UV warranty	Guaranteed not to fade when exposed to direct sunlight for a minimum of 3 years.
Outdoor use	Yes
Width	2 metres
Roll length	25 metres
Number of colours	5 in each profile
Static properties	Anti-static fibres used throughout
Exposure to water	Waterproof and rotproof
Fire resistance	AS9239.1:2003: CHF Value: 5.1kW/m ² . Smoke value: 73% min. Suitable for any class of building. AS/NZS 1530.3 Early Fire Hazards Test - Complies for New Zealand
Adhesive	Indoor: Karndean Fiba-Bond Outdoor: Karndean Fiba-Bond UV
Guarantee	5 Year indoor commercial heavy duty wear guarantee

Karndean International NZ

Unit A, 73 Greenmount Drive
East Tamaki, Auckland
P: 0800 44 21 01

E: info@karndean.co.nz

W: www.karndean.co.nz

